

# GT-D1M (TC-RB) DOOR TYPE

THE BASELINE OF A DURABLE DISHWASHER



## POWER

POWERFUL washing standards. Sustained pressure to deliver extraordinary results. Selectable wash timing. Stainless steel impellers housing.



## DURABLE

Stainless steel chamber build. Built from industrial grade 304 stainless steel. ENDURING performance with zero-trouble experience.



## DYNAMIC

Electrical components are resistant against the extreme environment and kitchen settings it is put into. It delivers CONSISTENT results everywhere.



## BUILT-IN

Same power delivery as the Standard Model, but now in an entire COMPLETE package with chemical dispensers.



## TECHNICAL DATA

### Model:

GT-D1M (LE-RB) 1 phase model | GT-D1M (LE-RB/BD) 1 phase model

GT-D1M (TC-RB) 3 phase model | GT-D1M (TC-RB/BD) 3 phase model

### Dimensions (mm):

697 (W) x 690 (D) x 1585 (H)

697 (W) x 690 (D) x 1625 (H)

### Loading height (mm):

310

### Rack type (mm):

500 x 500

### Machine net weight

68 kg

## OPERATING INFORMATION

### Wash temperature:

55°C - 65°C

### Rinse temperature:

82°C - 90°C

### Wash cycle (per rack):

60/90 seconds (selectable)

70/100 seconds (selectable) for 1 phase models

### Wash rate (per hour):

60/40 racks

50/36 racks for 1 phase models

### Rinse usage:

<2.0 liters per cycle

### Wash tank capacity:

36.0 liters



### Booster tank capacity:

10.0 liters



### Chemical dispensers:

Add-on feature (sold separately)

GT-D1M (TC-RB)



GT-D1M (TC-RB/BD)



## ELECTRICAL SPECIFICATIONS

Voltage supply	Booster tank	Wash tank	Wash pump	Total power loading
220V - 240V, 50/60Hz, 1 Phase	2.0 kW	2.0 kW	0.9 kW	<b>3.5 kW, 15.0 A (Alternative Heating)</b> 5.5 kW, 24.0 A (Full Heating)
380V - 415V, 50/60Hz, 3 Phase	9.0 kW	3.0 kW	0.9 kW	<b>11.0 kW, 19.1 A (Alternative Heating)</b> 14.0 kW, 25.0 A (Full Heating)
220V - 240V, 60Hz, 3 Phase	9.0 kW	3.0 kW	0.9 kW	<b>11.0 kW, 30.0 A (Alternative Heating)</b> 14.0 kW, 40.0 A (Full Heating)